

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Genesolv® SF
MSDS Number : 000000011248
Product Use Description : Solvent

Company : Honeywell International, Inc.
101 Columbia Road
Morristown, NJ 07962-1057

For more information call : 800-522-8001
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-651-523-0309
: Transportation: 1-800-424-9300 or +1-703-527-3887
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Liquefied gas

Color : colourless

Odor : slight sweet ether-like

Hazard Summary : **WARNING!** Contains gas under pressure; may explode if heated. This product is not flammable at ambient temperatures and atmospheric pressure. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating. Inhalation may cause central nervous system effects. May cause cardiac arrhythmia. May cause drowsiness and dizziness. Do not breathe vapour. May cause eye irritation. Avoid contact with skin, eyes and clothing. At higher temperatures, (>250 C), decomposition products may include hydrofluoric acid (HF) and carbonyl halides. The ACGIH Threshold Limit Values (2007) for Hydrogen Fluoride are TLV-TWA 0.5 ppm and Ceiling Exposure Limit 2 ppm.

Potential Health Effects

Skin : No skin irritation

Eyes : May cause eye irritation.

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

- Ingestion : Unlikely route of exposure.
Effects due to ingestion may include:
Gastrointestinal discomfort
- Inhalation : May cause cardiac arrhythmia.
Causes asphyxiation in high concentrations. The victim will not realize that he/she is suffocating.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Vapours may cause drowsiness and dizziness.
Inhalation may cause central nervous system effects.
- Chronic Exposure : None known.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration
1,1,1,3,3-Pentafluoropropane	460-73-1	100.00%

SECTION 4. FIRST AID MEASURES

- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If symptoms persist, call a physician. Take off all contaminated clothing immediately. Wash contaminated clothing before re-use.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
- Ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Call a physician immediately.

Notes to physician

- Treatment : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

SECTION 5. FIREFIGHTING MEASURES

- Flash point : None
- Ignition temperature : 412 °C (774 °F)
- Lower explosion limit : None
- Upper explosion limit : None
- Suitable extinguishing media : The product is not flammable. ASHRAE 34
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : This product is not flammable at ambient temperatures and atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Exposure to decomposition products may be a hazard to health.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO₂)
Carbonyl halides
- Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Remove all sources of ignition.
Vapours are heavier than air and can cause suffocation by

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

- reducing oxygen available for breathing.
Ensure adequate ventilation.
- Environmental precautions : Should not be released into the environment.
Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

- Handling : Handle with care.
Do not get in eyes, on skin, or on clothing.
Do not use in areas without adequate ventilation.
Perform filling operations only at stations with exhaust ventilation facilities.
Open drum carefully as content may be under pressure.
Do not breathe vapours or spray mist.
- Advice on protection against fire and explosion : Can form a combustible mixture with air at pressures above atmospheric pressure.
Keep product and empty container away from heat and sources of ignition.

Storage

- Requirements for storage areas and containers : Store away from incompatible substances.
Keep away from direct sunlight.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Ensure adequate ventilation, especially in confined areas.
Keep in original packaging, tightly closed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Do not breathe vapours or spray mist.
Avoid contact with skin, eyes and clothing.
- Engineering measures : Use with local exhaust ventilation.

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

- Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Impervious butyl rubber gloves
Neoprene gloves
Gloves must be inspected prior to use.
Replace when worn.
- Skin and body protection : Wear as appropriate:
Solvent-resistant gloves
Solvent-resistant apron and boots
If splashes are likely to occur, wear:
Protective suit
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes and clothing.
Ensure adequate ventilation, especially in confined areas.
Remove and wash contaminated clothing before re-use.
Contaminated work clothing should not be allowed out of the workplace.
Keep working clothes separately.
Wash hands before breaks and immediately after handling the product.

Exposure Guidelines

1,1,1,3,3-Pentafluoropropane 460-73-1 WEEL TWA 300 ppm 1,644 mg/m³

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquefied gas
- Color : colourless
- Odor : slight sweet ether-like
- Molecular Weight : 134 g/mol

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

pH	:	neutral
Freezing point	:	<-103 °C (-153 °F)
Boiling point/boiling range	:	15 °C (59 °F)
Vapor pressure	:	1,227 hPa at 20 °C (68 °F)
Vapor pressure	:	3,882 hPa at 54.4 °C (129.9 °F)
Relative vapour density	:	4.6 (Air = 1.0)
Density	:	1.32 g/cm ³ at 20 °C (68 °F)
Water solubility	:	7.8 g/l at 20 °C (68 °F)
Partition coefficient: n-octanol/water	:	log Pow: 1.35 at: 21.5 °C (70.7 °F)

SECTION 10. STABILITY AND REACTIVITY

Conditions to avoid	:	Protect from heat/overheating. Keep away from direct sunlight. Heat, flames and sparks.
Materials to avoid	:	Strong acids and strong bases Finely divided aluminium Sodium Potassium Calcium Magnesium Zinc Barium Lithium Strong oxidizing agents
Hazardous decomposition products	:	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide Carbon dioxide (CO ₂) Carbonyl halides Hydrogen fluoride
Thermal decomposition	:	>250 °C
Hazardous reactions	:	Hazardous polymerisation does not occur. Stable under normal conditions.

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

SECTION 11. TOXICOLOGICAL INFORMATION

- Acute inhalation toxicity : LC50: > 200000 ppm
Exposure time: 4 h
Species: rat
Note: No deaths Evidence of transient anesthetic effect.
- : LC50: > 100000 ppm
Exposure time: 4 h
Species: mouse
Note: No deaths Evidence of transient underactivity during exposure.
- Acute dermal toxicity : LD50: > 2,000 mg/kg
Species: rabbit
- Sensitisation : Cardiac sensitization
Species: dogs
Note: No effects noted at 35,000 ppm, the threshold for induction of cardiac arrhythmias in the presence of injected adrenalin was 44,000 ppm. no data available
- Repeated dose toxicity : Species: rat
NOAEL (No observed adverse effect level): 50000 ppm
Method: Embryotoxicity
Note: Not a teratogen
- : Species: rat (pups)
NOAEL (No observed adverse effect level): 50000 ppm
- : Species: rat (dams)
NOAEL (No observed adverse effect level): 2000 ppm
Note: due to decrease in body weight gains at 10,000 ppm and 50,000 ppm
- : Species: rat
Method: 2 Generation Inhalation Toxicity
Note: Exposures 6hrs/day, 7 days/wk at 0(control), 2000, 10,000 and 50,000 ppm.
- : Species: rat (dams)
Note: Toxicity seen in dams at 10,000 and 50,000 ppm and in pups at 50,000 ppm. Increased mortality late in the lactation phase of the study.
- : Species: rat

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

Note: 28-day Inhalation Study NOAEL (No observed adverse effect level) - 50,000 ppm NOEL - 500 ppm Dose levels: 0,500, 2000, 10,000 and 50,000 ppm

: Species: rat

Note: 90-day Inhalation Study Dose levels: 0,500, 2000, 10,000 and 50,000 ppm NOAEL (No observed adverse effect level) - 2,000 ppm

: Note: Overall, subchronic studies showed dose-related increases in urinary fluoride levels, urine volumes and water consumption. Increases were noted in hematological parameters, BUN levels and serum liver enzyme activities (GOT, GPT). These increases did not follow a dose response; however, they indicate that HFC-245fa is metabolized in the liver. Significant recovery was noted in these parameters following a 2-week, non-exposure period which followed the 28-day exposure period. No histopathological effects were noted in the 28-day study. The 90-day study noted an increase in incidence and severity (trace to moderate) of myocarditis (inflammation of the heart muscle) at 10,000 and 50,000 ppm. This was not noted at the 500 or 2,000 ppm dose levels nor was it seen the 28-day study at 50,000 ppm.

Genotoxicity in vitro

: Cell type: Human lymphocytes

Result: Weak positive activation without S9 at 30% v/v; not active with S9 up to 70% v/v.

: Test Method: Ames test

Metabolic activation: with or without metabolic activation

Result: negative

Genotoxicity in vivo

: Species: mouse

Cell type: Bone marrow

Application Route: Inhalation

Method: Mutagenicity (micronucleus test)

Result: negative

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish

: EC50: > 81.8 mg/l

Exposure time: 96 h

Species: *Oncorhynchus mykiss* (rainbow trout)

: NOEC: > 10 mg/l

Exposure time: 96 h

Species: *Oncorhynchus mykiss* (rainbow trout)

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

Toxicity to daphnia and other aquatic invertebrates. : EC50: > 97.9 mg/l
Exposure time: 48 h
Species: Daphnia

: NOEC: > 97.9 mg/l
Exposure time: 48 h
Species: Daphnia magna (Water flea)

Toxicity to algae : Growth inhibition
EC50: > 118 mg/l
Species: Algae
Method: OECD Test Guideline 201

Further information on ecology

Additional ecological information : This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82.
This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.
Refer to sections 610 and 612 for list of acceptable and unacceptable uses for this product.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Information: Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 3163
Proper shipping name : LIQUEFIED GAS, N.O.S.
(1,1,1,3,3-Pentafluoropropane)
Class : 2.2
Packing group :
Hazard Labels : 2.2

IATA UN/ID No. : UN 3163
Description of the goods : LIQUEFIED GAS, N.O.S.
(1,1,1,3,3-Pentafluoropropane)
Class : 2.2
Hazard Labels : 2.2
Packing instruction (cargo aircraft) : 200
Packing instruction (passenger aircraft) : 200

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

IMDG	UN/ID No.	: UN 3163
	Description of the goods	: LIQUEFIED GAS, N.O.S. (1,1,1,3,3-PENTAFLUOROPROPANE)
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C
	Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

Inventories

1907/2006 (EU)	: This mixture contains only ingredients which have been registered according to Regulation (EC) No. 1907/2006 (REACH).
US. Toxic Substances Control Act	: On TSCA Inventory
Australia. Industrial Chemical (Notification and Assessment) Act	: On the inventory, or in compliance with the inventory
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 144)	: All components of this product are on the Canadian DSL list.
Japan. Kashin-Hou Law List	: On the inventory, or in compliance with the inventory
Korea. Existing Chemicals Inventory (KECI)	: On the inventory, or in compliance with the inventory
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act	: Not in compliance with the inventory
China. Inventory of Existing Chemical Substances	: 1,1,1,3,3-Pentafluoropropane 460-73-1 : On the inventory, or in compliance with the inventory
NZIOC - New Zealand	: On the inventory, or in compliance with the inventory

National regulatory information

SARA 311/312 Hazards	: Acute Health Hazard Sudden Release of Pressure Hazard
-----------------------------	--

Material Safety Data Sheet

Genesolv SF 50lb/22.7kg Jug

Version 2

Revision Date 02/16/2012

California Prop. 65 : This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

WHMIS Classification : A
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0